GRANITE TREE RING INSTRUCTIONS / MATERIALS

ENCORE STONE PRODUCTS



48" Outside Diameter 36" Inside Diameter 10" High

117 Stones in Kit (5 extra) 14 Stones per row. 8 Rows High (1.25" per row)

MATERIALS NEEDED:

- Shovel
- Level
- Tape Measure
- Paver Base
- Construction Adhesive
- Gloves

- Mulch/Dirt
- Spray Paint
- Chalk
- Tamper
- Silicone GunRubber Mallet

ASSEMBLY STEPS



Select location for your Tree Ring, if using lawn/dirt location mark a 48" circle on surface and dig 2" down. Use level to ensure your base is even.



Put approx 2" of paver base into your circle - this MUST be tamped level before laying Encore Stones.



Select 14 stones you will use for your top row and set them to the side.* Then take 14 more stones and lay them on top of (the outer edge) of paver base-rough side facing up. Stones will have small gaps between joints when laid; which allows for drainage.



Once the first row is laid, apply a bead of construction adhesive to middle of stones and lay second row on top of first row (always rough side facing up), staggering joints as shown in picture above.



Repeat step #4 for rows 3-8, using the first 14 pieces you set aside for row #8(Don't forget- install rough side up). Stop every 2 rows and use rubber mallet to tap any pieces that may have shifted before the construction adhesive fully cures.



Once Tree Ring is built, add bags of mulch or dirt (whichever you prefer) to center and installation is complete. Before using- check construction adhesive tube for exact cure time.

Office: 386-236-0345 Fax: 386-236-0346 www.encorestone.com



^{*}Rough side up is recommended for top row